



Type	Capacity (Mcal)	Capacity (kW)	Water vol. (Ltr.)	Weight (kg)	H.S. (m2)	Gassided Vol. (m3)	dp (mmWC)	A	B1	C	D	E	F	G1	H	J	K	L	M	N	P	R	S1	T1	B2	G2	S2	T2	U	Excellent cond. TYPE
CLW 40	1000	1200	3220	4150	40	2,2	60	3425	4310	1650	2035	1125	800	300	1000	DN125-PN6	2x2"	50	2"	2080	265	420	2033	510	4355	300	2506	369	1125	L12C
CLW 50	1200	1500	3930	4800	50	2,7	55	3425	4310	1800	2180	1200	880	350	1250	DN150-PN6	2x2"	50	2"	2230	285	420	2213	570	4355	350	2674	505	1200	L18C
CLW 60	1500	1800	5140	6000	60	3,5	60	4230	5115	1850	2223	1218	900	400	1100	DN150-PN6	2x2"	65	2"	2273	310	420	2553	595	5160	350	2692	470	1218	L18C
CLW 75	2000	2400	5950	6800	75	4,7	62	4230	5115	2000	2373	1293	1000	450	1100	DN150-PN6	2x2"	65	2"	2423	335	580	2401	575	5160	450	2767	505	1293	L24C
CLW 95	2500	3000	7050	8250	95	5,65	60	4230	5165	2200	2573	1393	1150	500	1250	DN200-PN6	2x2"	65	2"	2623	360	580	2620	565	5160	450	2919	435	1393	L30C
CLW 115	3000	3600	7830	9120	115	6,4	60	4230	5215	2316	2689	1451	1200	550	1250	DN200-PN6	3x2"	65	2"	2739	380	580	2734	580	5160	500	3077	405	1451	L36C
CLW 130	3500	4200	9950	10630	130	8	68	5205	6320	2336	2728	1480	1200	600	1250	DN200-PN6	3x2"	80	2"	2778	380	580	2763	600	6215	550	3161	465	1480	L42C
CLW 145	4000	4800	11270	11380	145	8,9	68	5205	6370	2456	2848	1540	1250	650	1500	DN200-PN6	3x2"	80	2"	2898	400	580	2883	623	6215	600	3221	473	1540	L48C
CLW 155	4500	5400	11380	12030	155	9,9	76	5205	6420	2526	2918	1575	1350	700	1500	DN250-PN10	4x2"	80	2"	2968	400	580	2963	630	6215	650	3246	503	1575	L60C
CLW 170	5000	6000	11910	13500	170	10,75	76	5205	6420	2600	2992	1612	1400	700	1500	DN250-PN10	4x2"	80	2"	3042	400	700	3025	645	6215	650	3283	490	1612	L60C
CLW 185	5500	6600	12850	14460	185	12,3	80	5480	6745	2660	3052	1642	1450	700	1500	DN250-PN10	4x2"	100	2"	3102	400	700	3100	668	6540	700	3313	550	1642	L72C
CLW 200	6000	7200	13460	15600	200	13	80	5480	6795	2730	3122	1677	1500	750	1700	DN250-PN10	2xDN80-16	100	2"	3172	400	700	3170	705	6540	700	3348	545	1677	L72C
CLW 220	7000	8400	15280	17450	225	15,8	90	5890	7255	2840	3251	1751	1600	800	1700	DN250-PN10	2xDN100-16	100	2,5"	3301	470	830	3284	735	6950	700	3402	550	1751	L84C
CLW 250	8000	9600	16750	18650	250	16,6	98	6330	7745	2840	3251	1751	1600	850	1700	DN250-PN10	2xDN100-16	100	2,5"	3301	470	830	3285	735	7390	800	3572	600	1751	L96C
CLW 275	9000	10800	18750	20760	275	18,8	98	6330	7795	3000	3411	1831	1650	900	1900	DN300-PN10	2xDN100-16	125	2,5"	3461	500	830	3445	745	7390	850	3647	600	1831	L108C
CLW 300S	10000	12000	23700	25300	380	23	120	6900	8465	3190	3601	1426	1700	1000	2100	DN300-PN10	2xDN100-16	125	2,5"	3651	0	830	3600	0	7960	950	4197	0	2376	L120C
CLW 350S	12000	14000	25800	28100	420	25,7	120	6900	8465	3340	3751	1476	1800	1000	2250	DN300-PN10	2xDN125-16	125	2,5"	3801	0	830	3801	0	7960	950	4371	0	2500	L140C



Grote Esch 400
2841 MJ Moordrecht (NL) | Tel. +31(0)182 614 482 | e-mail : info@fhcrone.nl
fax +31(0)182 633 257 | website : www.fhcrone.eu

-Flange connections up to/incl. DN200 acc. EN1092-1 PN6 from DN250 acc. EN1092-1 PN10 Modifications reserved 2-2019
-Exportboilers or boilers from type CLW60 to CLW350S the boilers are provided with 2 lifting lugs.
-Flange connections safety valves acc. EN1092-1 PN16